

Product Name

R

(Linear)

Technical description

Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket and goniometer in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic in optical PC.



Supply

Drivers included and integrated.  
Voltage 230V AC 50Hz.  
Temperature -40° +45°

Installation

Wall and ceiling.

Applications

Churches, Museums, Shop windows, Facades decoration, Fair exhibitions

Size (mm)


250 x 176 x 42,6

Colour


Dark grey 4

Decay of the luminous flux

≥50.000 hr L890B10



Perimetral lighting



C0 / C180 C90 / C270

**IP66**




 Low Flicker
 
 2,1 Kg

Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L000R40HBLI40050	LED	50 W	5072 lm lm	8000 lm	4000 K	>80	HB	Dark grey	-

Accessories



Cable with connector  
Ca. 2m/Co. IP 2 poli  
LKITA00000000040  
Ca. 2m/Co. IP 3 poli  
LKITA00000000041



Ceiling Kit  
LKITA00000000060  
Galvanised iron  
LKITA00000000061  
Inox



Pole connection A  
Max 4 x R  
LKITA00000040001



Fast connector  
IP 2 poles  
LKITA00000000017



Fast connector  
IP 3 poles  
LKITA00000000003



Pole connection B  
LKITA00000040109

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.