


Product Name

H2

(T External driver)

Technical description

Suspension fitting which stands out by its characteristic cleanliness and elegance, H2 intends to bring together the most advanced technology solutions in a classic and traditional style. Thanks to these peculiarities, H2 finds its ideal habitat in the most varied applications; In fact, it can be installed in shops, exhibitions, commercial areas or industrial environments. Base in die cast aluminum alloy UNI EN 5076 polyester powder coated with aluminum reflector turned, anodized and polished. Stainless steel screws AISI 304. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80.



Supply

Driver mounted externally over the fitting to ensure optimum thermal performances. Available in ON-OFF, dimmable or DALI versions. Possibility to remote the driver for special applications. Voltage 230V AC 50Hz. Temperature -40° +45°

Installation

Suspended.

Applications

Commercial areas and industrial areas of small/medium size.

Size (mm)


Ø 430 x 375

Colour

Aluminium 6

Decay of the luminous flux

≥100.000 hr L80B20



IP66

 3,3 Kg

Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L00H24060BL60100	LED	100 W	9680 lm	16800 lm	4000 K	>80	60°	Aluminium	-
L00H24060DI60100	LED	100 W	9680 lm	16800 lm	4000 K	>80	60°	Aluminium	Dimmer
L00H24060DA60100	LED	100 W	9680 lm	16800 lm	4000 K	>80	60°	Aluminium	DALI

Accessories



Fast connector IP 2 poles
LKITA00000000017



Fast connector IP 3 poles
LKITA00000000003



Fast connector IP 5 poles
LKITA000000000103



Cable with connector
Ca. 2m/Co. IP 2 poli
LKITA00000000040
Ca. 2m/Co. IP 3 poli
LKITA00000000041

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.