


Product Name

Q2

(External driver)

Technical description

Q2 is an innovative and functional LED product with an industrial appeal, suitable for both indoor and outdoor illumination. It has been developed to satisfy the needs of commercial and industrial areas at their best. Body in die-cast aluminum alloy UNI EN 1706 painted with polyester powder. With bracket painted steel and goniometer in technopolymer with anti-rotation block in die-cast aluminum and powder painted. Screws made of 18/10 stainless steel. Tempered glass sodium-calcium type, 5 mm thickness. 91% transparency is guaranteed. Silicone gaskets. LED light source (lumileds), colour temperature (3000 K). High coefficient of performance chromatic CRI>80. Optic in optical PC.



Supply

External driver in Blank, dimmable or DALI.
Voltage 220-240V AC 50/60Hz.
Temperature -30°+45°

Installation

Wall, ceiling and suspended.

Applications

Commercial areas, Industrial areas, Warehouses, Production areas, Sport facilities

Size (mm)


466 x 251 x 101

Colour

Dark grey 4

Decay of the luminous flux

≥100.000 hr L80B20



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L00Q23090BL40170	LED	170 W	22780 lm	28560 lm	3000 K	>80	90°	Dark grey	-
L00Q23090DI40170	LED	170 W	22780 lm	28560 lm	3000 K	>80	90°	Dark grey	Dimmer
L00Q23090DA40170	LED	170 W	22780 lm	28560 lm	3000 K	>80	90°	Dark grey	DALI

Accessories



Suspension Kit
LKITA00000000004



Modules assembly kit
LKITA00000000005



Fast connector IP 2 poles
LKITA000000000017



Fast connector IP 3 poles
LKITA000000000003



Fast connector IP 5 poles
LKITA000000000103



Cable with connector
Ca. 2 m., Con 2 poles
LKITA000000000040
Ca. 2 m., Con 3 poles
LKITA000000000041



Pole mounting bracket
LKITA000000000002



90° Bracket kit
LKITA000000000020

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.