


Product Name

Q2

(External driver)

Technical description

Q2 is an innovative and functional LED product with an industrial appeal, suitable for both indoor and outdoor illumination. It has been developed to satisfy the needs of commercial and industrial areas at their best. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted polyester powder. Supplied with a painted galvanised steel bracket and goniometer in technopolymer with anti-rotation block in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Tempered glass sodium-calcium type, 5 mm thickness. 91% transparency is guaranteed. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic in optical PC.



Supply

External driver in ON-OFF, dimmable or DALI.
Voltage 220-240V AC 50/60Hz.
Temperature -40°+45°

Installation

Wall, ceiling and suspended.

Applications

Commercial areas, Industrial areas, Warehouses, Production areas, Sport facilities

Size (mm)


466 x 251 x 101

Colour

Dark grey 4

Decay of the luminous flux

≥100.000 hr L85B15



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L00Q24090BL40170	LED	170 W	21240 lm	29070 lm	4000 K	>80	90°	Dark grey	-
L00Q24090DI40170	LED	170 W	21240 lm	29070 lm	4000 K	>80	90°	Dark grey	Dimmer
L00Q24090DA40170	LED	170 W	21240 lm	29070 lm	4000 K	>80	90°	Dark grey	DALI

Accessories

LKITA00000000004	LKITA00000000005	LKITA00000000017	LKITA00000000003	LKITA00000000043 Inox LKITA00000000044	LKITA00000000040 Ca. 2 m., Con 3 poles LKITA00000000041	LKITA00000000020	LKITA00000000039	LKITA00000000093	LKITA00000040109

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.