

Product Name

Tm
(Linear)

Technical description

Tm is the smallest of round shape suspensions. Suitable for lighting of industrial environments and storage areas. It offers the possibility to be installed both in suspension and ceiling choosing between the possible installation kits. Body in die cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder coating. Stainless steel screws AISI 304. Silicone gasket and PC screen. Painted galvanized steel bracked with polyester powder available on request. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80.



Supply

Drivers included
Voltage 230V AC 50Hz.
Temperature -40° +45°

Installation

Suspended.

Applications

Relamping, Interior lighting, Commercial spaces

Size (mm)



Ø192 x 41

Colour

Dark grey 4

Decay of the luminous flux

≥50.000 hr L85B15



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour
L00TM4000LI40060	LED	60 W	6490 lm	9420 lm	4000 K	>80	120°	Dark grey

Accessories



Fast connector
IP 3 poles
LKITA00000000003



Ceiling kit
LKITA00000000013



Inox ceiling kit
LKITA00000100013



Cable with connector
Ca. 2 m., Con 2 poles
LKITA00000000040
Ca. 2 m., Con 3 poles
LKITA00000000041

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.