

Product Name

# Evo L

(External driver)

Technical description

Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted polyester powder. Supplied with a painted galvanised steel bracket and goniometer in technopolymer with anti-rotation block in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Silicone gaskets. On request, tempered glass sodium-calcium type, 5 mm thickness, 91% transparency. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI≥70. Optic in optical PC.

Supply

External driver (available in dimmable or DALI versions).  
Voltage 220-240V AC 50/60Hz.  
Temperature -40° +45°

Installation

Wall and ceiling

Applications

Commercial areas, Industrial areas, Sport facilities, Assembling areas

Size (mm)



522 x 322 x 136

Colour


Dark grey 4

Decay of the luminous flux

≥100.000 hr L85B15



▶▶ Top surface 0,11 m<sup>2</sup>      ▶▶ Side surface 0,02 m<sup>2</sup>



| Code                    | Source | Power | Lm (Output) | Lm (Tc=25°) | Temperature | CRI | Beams | Colour    | Control |
|-------------------------|--------|-------|-------------|-------------|-------------|-----|-------|-----------|---------|
| <b>LOEVL4AA2B140250</b> | LED    | 250 W | 34832 lm    | 45750 lm    | 4000 K      | ≥70 | A2    | Dark grey | -       |
| <b>LOEVL4AA2D140250</b> | LED    | 250 W | 34832 lm    | 45750 lm    | 4000 K      | ≥70 | A2    | Dark grey | Dimmer  |
| <b>LOEVL4AA2DA40250</b> | LED    | 250 W | 34832 lm    | 45750 lm    | 4000 K      | ≥70 | A2    | Dark grey | DALI    |

Accessories



Junction box kit  
LKITA00000100021



Laser pointer support kit  
LKITA00000000093



Fast connector IP 2 poles  
LKITA00000000017



Fast connector IP 3 poles  
LKITA00000000003

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.