

# Slice S

## L12 110A6 \_

### Technical description

Adjustable LED fitting for wall use and/or with stake, complete with bracket, extremely robust, with high IP protection, suitable for soft pointing lighting for indoor and outdoor use. This fitting is equipped with integrated LED modules.

Die-cast aluminium body, complete with lid and soft lens optic, screws in stainless steel AISI 304. Gasket in silicone rubber that provides a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source and colour temperature (2700K).

Very high coefficient of rendering >80CRI.

### Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 25000h / 25°

### Installation

Spot for outdoor

### Size (mm)



76 x 103 x 93

### Color

White  1 Grey  2 Dark Grey  4



IP65



| Code        | Source | Power | Luminous Flux | Temperature | CRI | Beams | Color     |
|-------------|--------|-------|---------------|-------------|-----|-------|-----------|
| L12 110A6 1 | LED    | 3 W   | 300 lm        | 2700 K      | >80 | 25°   | White     |
| L12 110A6 2 | LED    | 3 W   | 300 lm        | 2700 K      | >80 | 25°   | Grey      |
| L12 110A6 4 | LED    | 3 W   | 300 lm        | 2700 K      | >80 | 25°   | Dark Grey |

### Accessories



Stake  
L92 011000



Fast connector IP  
L93 043000