

Dakar

L15 01204 2

Symmetrical - Diffused
Large Beam - IP65

Technical description

Body and cover in die-cast aluminium (UNI 5076). Tempered glass, screen printed in white colour, sodic/calcic type, 5 mm thick. Fixed type glass equipped with 6 die cast aluminium plates with screw closing system. Reflector in pure aluminium, anodized and polished surface.

Installation

Industrial outdoor

Size (mm)



422 x 635 x 322

Colour

Grey **2**

 SINGLE    IP65   OPTIONAL   850°  NO GEAR 12,5 Kg

Code	Source	Tension	Power	Current	Connection	Lamp
L15 01204 2	High Sodium vapour	230 V	1000 W	10,3 A	E 40	ST SON-T
L15 01204 2	High Sodium vapour	230 V	1000 W	9,5 A	E 40	MT HQI-T/D



Included



Cassetta d'alimentazione inclusa: classe d'isolamento I, IP 65.
Accenditore alloggiato nella cassetta d'alimentazione
Gear box included: insulation class I, IP 65. Ignitor installed inside the gear box



Piastra d'alimentazione inclusa: classe d'isolamento I (applicazione in armadio elettrico). Accenditore alloggiato nel proiettore
Feeding plate included: insulation class I (application in cutout box). Ignitor installed inside the floodlight

Accessories



Griglia di protezione
Wire guard
Codice / code
L90 01700 0



Sezionatore a 3 vie
3 pole disconnecting switch
Codice / code
K10 00700 0