

Olympia 1000

L16 01201 2

Symmetrical - Diffused
Large Beam - IP65

Technical description

Body and side compartment in die-cast aluminium, UNI 5076 alloy. Tempered glass, sodic calcic type, 5 mm thick, heat-proof and shock-proof. Reflector in pure aluminium with hammered surface for the wide beam version and specular surface for the narrow beam version.

Installation

Industrial outdoor

Size (mm)



530 x 615 x 162

Colour

Grey 2

 SINGLE     IP65      850°  9 Kg

Code	Source	Tension	Power	Current	Connection	Lamp
L16 01201 2	Metal halide vapour	230 V	1000 W	9,5 A	E 40	MT HQI-T/D
L16 01201 2	High Sodium vapour	230 V	1000 W	10,3 A	E 40	ST SON-T



included



Cassetta d'alimentazione inclusa: classe d'isolamento I, IP 65.
Accenditore alloggiato nella cassetta d'alimentazione.
Gear box included: insulation class I, IP 65. Ignitor installed inside the gear box.

Accessories



Griglia di protezione
Wire guard
Codice / code
L90 01100 0



Raccordo per palo Ø 60mm horizontal position
Adaptator for pole Ø 60mm
Codice / code
L92 00500 0



Staffa raccordo per palo Ø 60mm vertical position
Bracket for pole Ø 60mm
Codice / code
L92 00200 0