

# Olympia 2

## L17 00604 2

Symmetrical - Diffused  
Large Beam - IP65

### Technical description

Body in die-cast aluminium, UNI 5076 alloy. Anti-loss hinges for the glass in grey thermo-plastic material. Tempered screen printed glass, white colour, sodic-calcic type, 5 mm thick, heat-proof and shock-proof. Reflector in pure aluminium, anodized and polished surface.

### Installation

Industrial outdoor

### Size (mm)



520 x 490 x 184

### Colour


Grey **2**

 SINGLE   CLASS II ON REQUEST   IP65     850° MAX  15,5 Kg

| Code        | Source              | Power | Current | Connection | Lampada       |
|-------------|---------------------|-------|---------|------------|---------------|
| L17 00604 2 | Metal halide vapour | 250 W | 3 A     | E 40       | MT HPI-T PLUS |



### Accessories



**Griglia di protezione**  
*Wire guard*

Codice / code  
L90 01100 0



Staffa braccio a sbalzo L: 500mm  
*Arm bracket L: 500mm*

Codice / code  
L92 00000 0



Staffa raccordo per palo Ø 60mm vertical position  
*Bracket for pole Ø 60mm*

Codice / code  
L92 00200 0



Raccordo per palo Ø 60mm  
*Adapter for pole Ø 60mm*

Codice / code  
L92 00500 0



Staffa braccio a sbalzo L: 1000mm  
*Arm bracket L: 1000mm*

Codice / code  
L92 00100 0



R7s HD max 150W con commutatore  
*R7s HD max 150W with converter*

Codice / code  
K10 00200 0