

# Olympia 2

## L17 00605 2

Asymmetrical  
IP65

### Technical description

Body in die-cast aluminium, UNI 5076 alloy. Anti-loss hinges for the glass in grey thermo-plastic material. Tempered screen printed glass, white colour, sodic-calcic type, 5 mm thick, heat-proof and shock-proof. Reflector in pure aluminium, anodized and polished surface.

### Installation

Industrial outdoor

### Size (mm)



520 x 490 x 184

### Colour

Grey **2**



| Code        | Source              | Power | Current | Connection | Lampada       |
|-------------|---------------------|-------|---------|------------|---------------|
| L17 00605 2 | Metal halide vapour | 250 W | 3 A     | E 40       | MT HPI-T PLUS |



### Accessories




Griglia di protezione  
Wire guard  
Codice / code  
L90 01100 0



Raccordo per palo Ø 60mm horizontal  
Adaptator for pole Ø 60mm  
Codice / code  
L92 00500 0



Staffa braccio a sbalzo L: 500mm  
Arm bracket L: 500mm  
Codice / code  
L92 00000 0



Staffa braccio a sbalzo L: 1000mm  
Arm bracket L: 1000mm  
Codice / code  
L92 00100 0



Staffa raccordo per palo Ø 60mm vertical position  
Bracket for pole Ø 60mm  
Codice / code  
L92 00200 0



R7s HD max 150W con commutatore  
R7s HD max 150W with converter  
Codice / code  
K10 00200 0