

Olympia 2

L17 00804 2

Symmetrical - Diffused
Large Beam - IP65

Technical description

Body in die-cast aluminium, UNI 5076 alloy. Anti-loss hinges for the glass in grey thermo-plastic material. Tempered screen printed glass, white colour, sodic-calcic type, 5 mm thick, heat-proof and shock-proof. Reflector in pure aluminium, anodized and polished surface.

Installation

Industrial outdoor

Size (mm)



520 x 490 x 184

Colour

Grey **2**



Code	Source	Power	Current	Connection	Lampada
L17 00804 2	High sodium vapour	400 W	4,4 A	E 40	ST SON-T



Accessories



Griglia di protezione
Wire guard

Codice / code
L90 01100 0




Raccordo staffa per palo Ø 60mm vertical position
Adapter for pole Ø 60mm

Codice / code
L92 00500 0



Staffa braccio a sbalzo L: 500mm
Arm bracket L: 500mm

Codice / code
L92 00000 0



Staffa braccio a sbalzo L: 1000mm
Arm bracket L: 1000mm

Codice / code
L92 00100 0



Staffa raccordo per palo Ø 60mm vertical position
Bracket for pole Ø 60mm

Codice / code
L92 00200 0



R7s HD max 150W con commutatore
R7s HD max 150W with converter

Codice / code
K10 00200 0