

Olympia 2

L17 00805 2

Asymmetrical
IP65

Technical description

Body in die-cast aluminium, UNI 5076 alloy. Anti-loss hinges for the glass in grey thermo-plastic material. Tempered screen printed glass, white colour, sodic-calcic type, 5 mm thick, heat-proof and shock-proof. Reflector in pure aluminium, anodized and polished surface.

Installation

Industrial outdoor

Size (mm)



520 x 490 x 184

Colour


Grey **2**



Code	Source	Power	Current	Connection	Lampada
L17 00805 2	High sodium vapour	400 W	4,4 A	E 40	ST SON-T



Accessories



Griglia di protezione
Wire guard
Codice / code
L90 01100 0




Staffa braccio a sbalzo L: 500mm
Arm bracket L: 500mm
Codice / code
L92 00000 0



Staffa raccordo per palo Ø 60mm vertical position
Bracket for pole Ø 60mm
Codice / code
L92 00200 0



Raccordo per palo Ø 60mm horizontal
Adaptator for pole Ø 60mm
Codice / code
L92 00500 0



Staffa braccio a sbalzo L: 1000mm
Arm bracket L: 1000mm
Codice / code
L92 00100 0



R7s HD max 150W con commutatore
R7s HD max 150W with converter
Codice / code
K10 00200 0