

Daytona

L1A 02304 2

Symmetrical - Diffused
Large Beam - IP65

Technical description

Body and cover in die-cast aluminium (UNI 5076). Tempered glass, screen printed in white colour, sodic/calcic type, 5 mm thick. Fixed type glass equipped with 6 die cast aluminium plates with screw closing system. Reflector in pure aluminium, anodized and polished.

Installation

Industrial outdoor

Size (mm)



690 x 815 x 430

Colour

Grey **2**

 SINGLE     IP65    OPTIONAL    850°  NO GEAR 17 Kg

Code	Source	Tension	Power	Current	Connection	Lamp
L1A 02304 2	Metal halide vapour	380 V	2000 W	8,8 A	E 40	MT HQI-T/N 



Included



Cassetta d'alimentazione inclusa: classe d'isolamento I, IP 65.
Accenditore alloggiato nella cassetta d'alimentazione
Gear box included: insulation class I, IP 65. Ignitor installed inside the gear box



Piastra d'alimentazione inclusa: classe d'isolamento I (applicazione in armadio elettrico). Accenditore alloggiato nel proiettore
Feeding plate included: insulation class I (application in cutout box). Ignitor installed inside the floodlight

Accessories



Griglia di protezione
Wire guard
Codice / code
L90 01300 0



Sezionatore a 3 vie
3 pole disconnecting switch
Codice / code
K10 00700 0