

Pilot

L1C 01430 2

Asymmetrical
Wide Type 45° - IP65

Technical description

Fixed glass with blocking plaques tightened by screw. Body and rear cover in die cast aluminum UNI 5076 alloy. Tempered clear glass sodic/calcic type. Reflector in extra-pure aluminum, anodized and polished surface.

Installation

Industrial outdoor

Size (mm)

840 x 635 x 390

Colour

Grey **2**

 SINGLE    IP65    K12.5 x 75    850°  19,5 Kg

Code	Source	Tension	Power	Current	Connection	Lamp
L1C 01430 2	Metal halide vapour	380 V	2000 W	8,8 A	E 40	MT HQI-T/N/E SU

included



Cassetta d'alimentazione inclusa: classe d'isolamento I, IP 65.
Accenditore alloggiato nella cassetta d'alimentazione.
Gear box included: insulation class I, IP 65. Ignitor installed inside the gear box.

Optional




Piastra d'alimentazione inclusa: classe d'isolamento I (applicazione in armadio elettrico). Accenditore alloggiato nel proiettore.
Feeding plate included: insulation class I (application in cutout box). Ignitor installed inside the floodlight.

Accessories



Griglia di protezione
Wire guard
Codice / code
L90 01600 0



► 0,37 m² ► 0,17 m²

