

Pilot

L1C 01535 2

Asymmetrical

Wide Type 55° - IP65

Technical description

Fixed glass with blocking plaques tightened by screw. Body and rear cover in die cast aluminum UNI 5076 alloy. Tempered clear glass sodic/calcic type. Reflector in extra-pure aluminum, anodized and polished surface.

Installation

Industrial outdoor

Size (mm)

840 x 635 x 390

Colour

Grey **2**

 SINGLE
 


IP65






850°
 **19,5 Kg**

Code	Source	Tension	Power	Current	Connection	Lamp
L1C 01535 2	Metal halide vapour	380 V	2000 W	10,3 A	CABLE	MD HQ/TS/D/S

included



Cassetta d'alimentazione inclusa: classe d'isolamento I, IP 65.
 Accenditore alloggiato nella cassetta d'alimentazione.
 Gear box included: insulation class I, IP 65. Ignitor installed inside the gear box.

Optional



Piastra d'alimentazione inclusa: classe d'isolamento I (applicazione in armadio elettrico). Accenditore alloggiato nel proiettore.
 Feeding plate included: insulation class I (application in cutout box). Ignitor installed inside the floodlight.

Accessories



Griglia di protezione
 Wire guard

Codice / code
 L90 01600 0

