

# Blade 1

## L3B 313AD \_

### Technical description

Fixed LED fitting for recessed floor use, extremely robust with high IP protection and various degrees openings. Suitable for indoor and outdoor use. This fitting is equipped with integrated LED modules. Body in die-cast aluminium. Flat tempered glass diffuser. Screws and nut in stainless steel AISI 304. Reflector in anodized aluminium with various degrees openings. Fitting complete with formwork in thermoplastic material. Gasket in silicone rubber that provides a high resistance to water splashes. Powder paint with high resistance to external agents. . LED light source and colour temperature (4000K Neutral White ). Very high coefficient of rendering >80CRI.

### Supply

Driver included.  
Input voltage 220-240 V AC/50-60Hz  
Temperature -20° +40°  
Life 30000h / 25°

### Installation

Recessed for outdoor

### Size (mm)


297 x 54 x 76

### Color


White 1    Grey 2    Dark Grey 4

  IP65

| Code        | Source | Power     | Luminous Flux | Temperature | CRI | Beams | Color     |
|-------------|--------|-----------|---------------|-------------|-----|-------|-----------|
| L3B 313AD 1 | LED    | 0.5 W x10 | 500 lm        | 4000 K      | >80 | 60°   | White     |
| L3B 313AD 2 | LED    | 0.5 W x10 | 500 lm        | 4000 K      | >80 | 60°   | Grey      |
| L3B 313AD 4 | LED    | 0.5 W x10 | 500 lm        | 4000 K      | >80 | 60°   | Dark Grey |



 260x26mm



### Accessories



Fast connector IP  
L93 043000