

Product Name

# Evo 3XL

(External driver)

Technical description

Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted polyester powder. Supplied with a painted galvanised steel bracket and goniometer in technopolymer with anti-rotation block in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Silicone gaskets. On request, tempered glass sodium-calcium type, 5 mm thickness, 91% transparency. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI≥70. Optic in optical PC.

Supply

External driver (available in dimmable or DALI versions).  
Voltage 220-240V AC 50/60Hz.  
Temperature -40° +45°

Installation

Wall and ceiling

Applications

Commercial areas, Industrial areas, Sport facilities, Assembling areas

Size (mm)



814 x 322 x 136

Colour

Dark grey 4

Decay of the luminous flux

≥100.000 hr LM85B20



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
<b>L3EXL4AH7BL41050</b>	LED	1050 W	168105 lm	184800 lm	4000 K	≥70	Sim. 60°	Dark grey	-
<b>L3EXL4AH7DI41050</b>	LED	1050 W	168105 lm	184800 lm	4000 K	≥70	Sim. 60°	Dark grey	Dimmer
<b>L3EXL4AH7DA41050</b>	LED	1050 W	168105 lm	184800 lm	4000 K	≥70	Sim. 60°	Dark grey	DALI

Accessories



Junction box kit  
LKITA00000100021



Laser pointer support kit  
LKITA00000000093



Fast connector IP 2 poles  
LKITA00000000017



Fast connector IP 3 poles  
LKITA00000000003

LANZINI indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.