


Product Name

# Evo 3XL

(External driver)

Technical description

Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted polyester powder. Supplied with a painted galvanised steel bracket and goniometer in technopolymer with anti-rotation block in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Silicone gaskets. On request, tempered glass sodium-calcium type, 5 mm thickness, 91% transparency. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI≥70. Optic in optical PC.



Supply

External driver (available in dimmable or DALI versions).  
Voltage 220-240V AC 50/60Hz.  
Temperature -40° +45°

Installation

Wall and ceiling

Applications

Commercial areas, Industrial areas, Sport facilities, Assembling areas

Size (mm)


814 x 322 x 136

Colour

Dark grey 4

Decay of the luminous flux

≥100.000 hr LM85B20



| Code                    | Source | Power | Lm (Output) | Lm (Tc=25°) | Temperature | CRI | Beams    | Colour    | Control |
|-------------------------|--------|-------|-------------|-------------|-------------|-----|----------|-----------|---------|
| <b>L3EXL4AH9BL40900</b> | LED    | 900 W | 149826 lm   | 158400 lm   | 4000 K      | ≥70 | Sim. 30° | Dark grey | -       |
| <b>L3EXL4AH9DI40900</b> | LED    | 900 W | 149826 lm   | 158400 lm   | 4000 K      | ≥70 | Sim. 30° | Dark grey | Dimmer  |
| <b>L3EXL4AH9DA40900</b> | LED    | 900 W | 149826 lm   | 158400 lm   | 4000 K      | ≥70 | Sim. 30° | Dark grey | DALI    |

Accessories



Junction box kit  
LKITA00000100021



Laser pointer support kit  
LKITA00000000093



Fast connector IP 2 poles  
LKITA00000000017



Fast connector IP 3 poles  
LKITA00000000003

LANZINI indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.