

Icon T pla-M

L60 217A8 _

Technical description

Cylindrical shaped fixed LED fitting for ceiling use, unidirectional, extremely robust , with high IP protection, suitable for direct lighting of porches , canopies and transit areas for indoor and outdoor use. This fitting is equipped with integrated LED modules.

Die-cast aluminium body, complete with flat tempered glass diffuser that creates a pleasant coplanarity without any protrusion, screws in stainless steel AISI 304. Reflector in anodized aluminium with various degrees of openings. Gasket in silicone rubber that provides a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (3000K).

Very high coefficient of rendering >80CRI.

Supply

Driver included.

Input voltage 220-240 V AC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Ceiling fittings



Size (mm)

108 x 108 x 150

Color

White 1 Grey 2 Dark Grey 4

  IP54



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L60 217A8 1	LED COB	12 W	1200 lm	3000 K	>80	36°	White
L60 217A8 2	LED COB	12 W	1200 lm	3000 K	>80	36°	Grey
L60 217A8 4	LED COB	12 W	1200 lm	3000 K	>80	36°	Dark Grey