

Icon Q pla-M

L63 200A7 _

Technical description

Parallelepiped shaped fixed LED fitting for wall use, biemission, extremely robust, with high IP protection, suitable for direct and indirect lighting of facades, pillars and columns for indoor and outdoor use. This fitting is equipped with integrated LED modules.

Die-cast aluminium body, complete with flat tempered glass diffuser. Screws in stainless steel AISI 304. Reflector in anodized aluminium with various degrees of openings. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (3000K).

Very high coefficient of rendering >80CRI.

Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Ceiling fittings



Size (mm)

118 x 118 x 120

Color

White 1 Grey 2 Dark Grey 4

  IP54



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L63 200A7 1	LED COB	8 W	800 lm	3000 K	>80	30°	White
L63 200A7 2	LED COB	8 W	800 lm	3000 K	>80	30°	Grey
L63 200A7 4	LED COB	8 W	800 lm	3000 K	>80	30°	Dark Grey