

# Icon T Bi-M

## L77 120B8 \_

### Technical description

Cylindrical shaped fixed LED fitting for wall use, biemission, extremely robust, with high IP protection, suitable for direct and indirect lighting of facades, pillars and columns for indoor and outdoor use. This fitting is equipped with integrated LED modules.

Die-cast aluminium body, complete with flat tempered glass diffuser. Screws in stainless steel AISI 304. Reflector in anodized aluminium with various degrees of openings. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (2700K).

Very high coefficient of rendering >80CRI.

### Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

### Installation

Fittings for outdoor Wall

### Size (mm)

108 x 147 x 260

### Color

Grey **2**      Dark Grey **4**

  IP54 

| Code        | Source  | Power   | Luminous Flux | Temperature | CRI | Beams | Color     |
|-------------|---------|---------|---------------|-------------|-----|-------|-----------|
| L77 120B8 2 | LED COB | 12 W x2 | 2400 lm       | 2700 K      | >80 | 36°   | Grey      |
| L77 120B8 4 | LED COB | 12 W x2 | 2400 lm       | 2700 K      | >80 | 36°   | Dark Grey |

