

# Revers 1 - 350mm

## L81 183BE \_

### Technical description

Cylindrical shape fixed LED fitting with pole of various heights , extremely robust , with high IP protection , suitable for 2x80° degree direct lighting , for outdoor use , for gardens, paths and squares application. This fitting is equipped with integrated LED modules.

Body and top-pole in die-cast aluminium, complete with cylindrical diffuser in (PC) polycarbonate, screws in stainless steel AISI 304. Conical reflector in polished aluminium with rotationally symmetric wide distribution. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (2700K).

Very high coefficient of rendering >80CRI.

### Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

### Installation

Bollard

### Size (mm)



200 x 200 x 350

### Color

Grey **2** Dark Grey **4**



IP65



C0 / C180 C90 / C270 G0

| Code        | Source  | Power | Luminous Flux | Temperature | CRI | Beams | Colour    |
|-------------|---------|-------|---------------|-------------|-----|-------|-----------|
| L81 183BE 2 | LED COB | 12 W  | 1200 lm       | 2700 K      | >80 | 2x80° | Grey      |
| L81 183BE 4 | LED COB | 12 W  | 1200 lm       | 2700 K      | >80 | 2x80° | Dark Grey |

### Accessories



Fast connector IP  
L93 062000



Bolts ø180  
L92 012000