

Flat C - 1040mm

L83 182AJ _

Technical description

Cylindrical shape fixed LED fitting with pole of various heights , extremely robust , with high IP protection , suitable for 360° degree direct lighting , for outdoor use , for gardens, paths and squares application. This fitting is equipped with integrated LED modules.

Body and top-pole in die-cast aluminium, complete with cylindrical diffuser in (PC) polycarbonate , screws in stainless steel AISI 304. Conical reflector in polished aluminium with rotationally symmetric wide distribution. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source and colour temperature (2700K).

Very high coefficient of rendering >80CRI.

Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Bollard

Size (mm)



160 x 160 x 1040

Color

Grey **2** Dark Grey **4**



IP54



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L83 182AJ 2	LED	0.5 W x16	800 lm	2700 K	>80	360°	Grey
L83 182AJ 4	LED	0.5 W x16	800 lm	2700 K	>80	360°	Dark Grey

Accessories



Fast connector IP
L93 062000



Bolts ø180
L92 012000