

Flat C - 340mm

L83 280AJ _

Technical description

Cylindrical shape fixed LED fitting with pole of various heights , extremely robust , with high IP protection , suitable for 360° degree direct lighting , for outdoor use , for gardens, paths and squares application. This fitting is equipped with integrated LED modules.

Body and top-pole in die-cast aluminium, complete with cylindrical diffuser in (PC) polycarbonate , screws in stainless steel AISI 304. Conical reflector in polished aluminium with rotationally symmetric wide distribution. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source and colour temperature (3000K).

Very high coefficient of rendering >80CRI.

Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Bollard

Size (mm)



160 x 160 x 340

Color

Grey **2** Dark Grey **4**



IP54



| Code | Source | Power | Luminous Flux | Temperature | CRI | Beams | Color |
|-------------|--------|-----------|---------------|-------------|-----|-------|-----------|
| L83 280AJ 2 | LED | 0.5 W x16 | 800 lm | 3000 K | >80 | 360° | Grey |
| L83 280AJ 4 | LED | 0.5 W x16 | 800 lm | 3000 K | >80 | 360° | Dark Grey |

Accessories



Fast connector IP
L93 062000



Bolts ø180
L92 012000