

# Flat C - 1040mm

## L83 382AJ \_

### Technical description

Cylindrical shape fixed LED fitting with pole of various heights , extremely robust , with high IP protection , suitable for 360° degree direct lighting , for outdoor use , for gardens, paths and squares application. This fitting is equipped with integrated LED modules.

Body and top-pole in die-cast aluminium, complete with cylindrical diffuser in (PC) polycarbonate , screws in stainless steel AISI 304. Conical reflector in polished aluminium with rotationally symmetric wide distribution. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source and colour temperature (4000K Neutral White ).

Very high coefficient of rendering >80CRI.

### Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

### Installation

Bollard

### Size (mm)



160 x 160 x 1040

### Color

Grey **2** Dark Grey **4**



IP54



| Code        | Source | Power     | Luminous Flux | Temperature | CRI | Beams | Color     |
|-------------|--------|-----------|---------------|-------------|-----|-------|-----------|
| L83 382AJ 2 | LED    | 0.5 W x16 | 800 lm        | 4000 K      | >80 | 360°  | Grey      |
| L83 382AJ 4 | LED    | 0.5 W x16 | 800 lm        | 4000 K      | >80 | 360°  | Dark Grey |

### Accessories



Fast connector IP  
L93 062000



Bolts ø180  
L92 012000