

Dome C - 375mm

L86 180AJ _

Technical description

Cylindrical shape fixed LED fitting with pole of various heights , extremely robust , with high IP protection , suitable for 360° degree direct lighting , for outdoor use , for gardens, paths and squares application. This fitting is equipped with integrated LED modules.

Body and top-pole in die-cast aluminium, complete with cylindrical diffuser in (PC) polycarbonate, screws in stainless steel AISI 304.

Conical reflector in polished aluminium with rotationally symmetric wide distribution. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source and colour temperature (2700K).

Very high coefficient of rendering >80CRI.

Supply

Driver included.

Input voltage 220-240 V AC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Bollard

Size (mm)



160 x 160 x 375

Color

Grey **2** Dark Grey **4**



IP54



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L86 180AJ 2	LED	0.5 W x16	800 lm	2700 K	>80	360°	Grey
L86 180AJ 4	LED	0.5 W x16	800 lm	2700 K	>80	360°	Dark Grey

Accessories



Connettore rapido IP
L93 062000



Tirafondi ø180
L92 012000