

# Roll M

## LG1 203A9 \_

### Technical description

LED fitting for ceilings. Body in die cast aluminium. Anodized aluminium reflector with high luminous efficiency. This fitting is equipped with integrated LED modules.  
 Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100. Optics in anodized aluminium.  
 LED light source CREE COB and colour temperature ( 3000 K ).  
 Very high coefficient of rendering >90CRI.

### Supply

Driver included.  
 Input voltage 220-240 V AC/50-60Hz  
 Temperature -20° +40°  
 Life 30000h / 25°

### Installation

Ceiling.

### Size (mm)



140 x 140 x 180

### Colour

White ☐ 1 Grey ☐ 2 Dark grey ☐ 4



IP20



| Code        | Source   | Power | Luminous Flux | Temperature | CRI | Beams | Colour    |
|-------------|----------|-------|---------------|-------------|-----|-------|-----------|
| LG1 103A9 1 | COB CREE | 20 W  | 1427 lm       | 3000 K      | >90 | 40°   | White     |
| LG1 103A9 2 | COB CREE | 20 W  | 1427 lm       | 3000 K      | >90 | 40°   | Grey      |
| LG1 103A9 4 | COB CREE | 20 W  | 1427 lm       | 3000 K      | >90 | 40°   | Dark grey |