

L 2 Bi 1200 mm

LL2BI27BABL_0040

Technical description


LED fitting in extruded aluminum square section, direct mono emission, continuous form without structural interruptions, suitable in pendant version, ceiling, wall and recessed no frame. Polycarbonate diffuser with high luminous efficiency.

Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100.

Diffuser in white opaline polycarbonate. (120°).

LED light source and colour temperature (2700 K).

Very high coefficient of rendering >90CRI.



Supply

Driver included.

Input voltage 220-240 V AC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Suspension, ceiling, wall and recessed no frame.

Size (mm)

1200 x 51 x 75

Colour

White 1 Aluminium 6 Black 3

CE IP20 RoHS Flicker Free

Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Colour
LL2BI27BABL10040	LED	40 W	3400 lm	2700 K	>90	120°	White
LL2BI27BABL60040	LED	40 W	3400 lm	2700 K	>90	120°	Aluminium
LL2BI27BABL30040	LED	40 W	3400 lm	2700 K	>90	120°	Black

Accessories

1 BIANCO / WHITE 3 NERO / BLACK 6 ALLUMINIO / ALUMINIUM



Curve form 90°
(300x300)

LKITA00000000077




3-way form
(600x300)

LKITA000000_0069



4-way form
(600x600)

LKITA000000_0070



Retractable mechanical linear joints
LKITA00000000065



Hanging kit 1,5 m
LKITA00000000066



Power kit 1,5 m
LKITA00000000067



Wall mount kit
LKITA00000000073



Endcap
LKITA000000_0075