

L3 Bi 1200 mm

LL3BI30BABL_0040

Technical description


LED fitting in extruded aluminum square section, direct mono emission, continuous form without structural interruptions, suitable in pendant version, ceiling, wall and recessed no frame. Polycarbonate diffuser with high luminous efficiency.

Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100.

Diffuser in white opaline polycarbonate. (120°).

LED light source and colour temperature (3000 K).

Very high coefficient of rendering >90CRI.



Supply

Driver included.

Input voltage 220-240 V AC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Suspension, ceiling, wall and recessed no frame.

Size (mm)

1200 x 76 x 101

Colour

White 1 Aluminium 6 Black 3

CE IP20 RoHS Flicker Free

Codice	Sorgente	Potenza	Flusso Luminoso	Temperatura	CRI	Ottiche	Colore
LL3BI30BABL10040	LED	40 W	3400 lm	3000 K	>90	120°	White
LL3BI30BABL60040	LED	40 W	3400 lm	3000 K	>90	120°	Aluminium
LL3BI30BABL30040	LED	40 W	3400 lm	3000 K	>90	120°	Black

Accessories

1 BIANCO / WHITE 3 NERO / BLACK 6 ALLUMINIO / ALUMINIUM



Curve form 90°
(300x300)

LKITA000000000080




3-way form
(600x300)

LKITA000000_0081



4-way form
(600x600)

LKITA000000_0082



Retractable mechanical linear joints
LKITA000000000065



Hanging kit 1,5 m
LKITA000000000066



Power kit 1,5 m
LKITA000000000067



Wall mount kit
LKITA000000000085



Endcap
LKITA000000_0087