

Icon T pla-S

L60 100AD _

Technical description

Cylindrical shaped fixed LED fitting for ceiling use, unidirectional, extremely robust , with high IP protection, suitable for direct lighting of porches , canopies and transit areas for indoor and outdoor use. This fitting is equipped with integrated LED modules.

Die-cast aluminium body, complete with flat tempered glass diffuser that creates a pleasant coplanarity without any protrusion, screws in stainless steel AISI 304. Reflector in anodized aluminium with various degrees of openings. Gasket in silicone rubber that provides a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (2700K).

Very high coefficient of rendering >80CRI.

Supply

Driver included.

Input voltage 220-240 V AC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Ceiling fittings



Size (mm)

90 x 90 x 113

Color

White 1 Grey 2 Dark Grey 4

  IP54



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L60 100AD 1	LED COB	8 W	800 lm	2700 K	>80	60°	White
L60 100AD 2	LED COB	8 W	800 lm	2700 K	>80	60°	Grey
L60 100AD 4	LED COB	8 W	800 lm	2700 K	>80	60°	Dark Grey