

# Icon T pla-L

## L60 217AF \_

### Technical description

Cylindrical shaped fixed LED fitting for ceiling use, unidirectional, extremely robust , with high IP protection, suitable for direct lighting of porches , canopies and transit areas for indoor and outdoor use. This fitting is equipped with integrated LED modules. Die-cast aluminium body, complete with flat tempered glass diffuser that creates a pleasant coplanarity without any protrusion, screws in stainless steel AISI 304. Reflector in anodized aluminium with various degrees of openings. Gasket in silicone rubber that provides a high resistance to water splashes. Powder paint with high resistance to external agents. LED light source COB and colour temperature (3000K). Very high coefficient of rendering >80CRI.

### Supply

Driver included.  
Input voltage 220-240 V AC/50-60Hz  
Temperature -20° +40°  
Life 30000h / 25°

### Installation

Ceiling fittings



### Size (mm)

108 x 108 x 150

### Color

White 1    Grey 2    Dark Grey 4

  IP54



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L60 217AF 1	LED COB	12 W	1200 lm	3000 K	>80	90°	White
L60 217AF 2	LED COB	12 W	1200 lm	3000 K	>80	90°	Grey
L60 217AF 4	LED COB	12 W	1200 lm	3000 K	>80	90°	Dark Grey