

# Icon T Bi-M

## L77 320B8 \_

### Technical description

Cylindrical shaped fixed LED fitting for wall use, biemission, extremely robust, with high IP protection, suitable for direct and indirect lighting of facades, pillars and columns for indoor and outdoor use. This fitting is equipped with integrated LED modules.

Die-cast aluminium body, complete with flat tempered glass diffuser. Screws in stainless steel AISI 304. Reflector in anodized aluminium with various degrees of openings. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (4000K Neutral White ).

Very high coefficient of rendering >80CRI.

### Supply

Driver included.

Input voltage 220-240 V AC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

### Installation

Fittings for outdoor Wall

### Size (mm)

108 x 147 x 260

### Color

Grey **2**      Dark Grey **4**

  IP54 

Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L77 320B8 2	LED COB	12 W x2	2400 lm	4000 K	>80	36°	Grey
L77 320B8 4	LED COB	12 W x2	2400 lm	4000 K	>80	36°	Dark Grey

