

# Revers 2 - 900mm

## L80 285BE \_

### Technical description

Cylindrical shape fixed LED fitting with pole of various heights , extremely robust , with high IP protection , suitable for 2x80° degree biemission direct lighting, for outdoor use , for gardens, paths and squares application. This fitting is equipped with integrated LED modules. Body and top-pole in die-cast aluminium, complete with cylindrical diffuser in (PC) polycarbonate , screws in stainless steel AISI 304. Conical reflector in polished aluminium with rotationally symmetric wide distribution. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (3000K).

Very high coefficient of rendering >80CRI.

### Supply

Driver included.

Input voltage 220-240 V AC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

### Installation

Bollard

### Size (mm)



200 x 200 x 900

### Color

Grey **2** Dark Grey **4**



IP65



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L80 285BE 2	LED COB	12 W	1200 lm	3000 K	>80	2x80°	Grey
L80 285BE 4	LED COB	12 W	1200 lm	3000 K	>80	2x80°	Dark Grey

### Accessories



Connettore rapido IP  
Fast connector IP  
L93 062000



Tirafondi ø180  
Bolts ø180  
L92 012000