

# Revers 1 - 350mm

## L81 283BE \_

### Technical description

Cylindrical shape fixed LED fitting with pole of various heights , extremely robust , with high IP protection , suitable for 2x80° degree direct lighting , for outdoor use , for gardens, paths and squares application. This fitting is equipped with integrated LED modules.

Body and top-pole in die-cast aluminium, complete with cylindrical diffuser in (PC) polycarbonate, screws in stainless steel AISI 304. Conical reflector in polished aluminium with rotationally symmetric wide distribution. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (3000K).

Very high coefficient of rendering >80CRI.

### Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

### Installation

Bollard

### Size (mm)



200 x 200 x 350

### Color

Grey **2** Dark Grey **4**



IP65



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Colour
L81 283BE 2	LED COB	12 W	1200 lm	3000 K	>80	2x80°	Grey
L81 283BE 4	LED COB	12 W	1200 lm	3000 K	>80	2x80°	Dark Grey

### Accessories



Fast connector IP  
L93 062000



Bolts ø180  
L92 012000