

Dome P - 1080mm

L87 382AJ _

Technical description

Cylindrical shape fixed LED fitting with pole of various heights , extremely robust , with high IP protection , suitable for 360° degree direct lighting , for outdoor use , for gardens, paths and squares application. This fitting is equipped with integrated LED modules.

Body and top-pole in die-cast aluminium, complete with cylindrical diffuser in (PC) polycarbonate, screws in stainless steel AISI 304.

Conical reflector in polished aluminium with rotationally symmetric wide distribution. Gasket in silicone rubber which guarantees a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source and colour temperature (4000K Neutral White).

Very high coefficient of rendering >80CRI.

Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 30000h / 25°

Installation

Bollard

Size (mm)


160 x 160 x 1080

Color

Grey **2** Dark Grey **4**



IP54



C0 / C180 C90 / C270 G0

Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L87 382AJ 2	LED	8 W x1	800 lm	4000 K	>80	360°	Grey
L87 382AJ 4	LED	8 W x1	800 lm	4000 K	>80	360°	Dark Grey

Accessories



Fast connector IP
L93 062000



Bolts ø180
L92 012000