

# Pin S

## LD9 305A9 \_

### Technical description

LED fitting for false ceilings, body in die cast aluminium, aluminium reflector with high luminous efficiency adjustable  $\pm 20^\circ$ .  
 This fitting is equipped with integrated LED modules.  
 Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100. Optics in anodized aluminium.  
 LED light source CREE COB and colour temperature ( 4000K Neutral White ).  
 Very high coefficient of rendering  $>90\text{CRI}$ .

### Supply

Remote driver included.  
 Input voltage 220-240 V AC/50-60Hz  
 Temperature  $-20^\circ +40^\circ$   
 Life 30000h /  $25^\circ$

### Installation

Recessed for ceiling.

### Size (mm)


140 x 140 x 111

### Color

White ☐ 1 Grey ☒ 2



IP20



| Code        | Source   | Power | Luminous Flux | Temperature | CRI   | Beams      | Color |
|-------------|----------|-------|---------------|-------------|-------|------------|-------|
| LD9 305A9 1 | COB CREE | 35 W  | 2592 lm       | 4000 K      | $>90$ | $40^\circ$ | White |
| LD9 305A9 2 | COB CREE | 35 W  | 2592 lm       | 4000 K      | $>90$ | $40^\circ$ | Grey  |