

# Roll S

## LG0 302A1 \_

### Technical description

LED fitting for ceilings. Body in die cast aluminium. Anodized aluminium reflector with high luminous efficiency.  
This fitting is equipped with integrated LED modules.  
Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100. Optics in anodized aluminium.  
LED light source CREE COB and colour temperature ( 4000 K Neutral White ).  
Very high coefficient of rendering >90CRI.

### Supply

Driver included.  
Input voltage 220-240 V AC/50-60Hz  
Temperature -20° +40°  
Life 30000h / 25°

### Installation



Ceiling.

### Size (mm)

140 x 140 x 180

### Colour

White 1 Grey 2 Dark grey 4



| Code        | Source   | Power | Luminous Flux | Temperature | CRI | Beams | Colour    |
|-------------|----------|-------|---------------|-------------|-----|-------|-----------|
| LG0 302A1 1 | COB CREE | 15 W  | 960 lm        | 4000 K      | >90 | 10°   | White     |
| LG0 302A1 2 | COB CREE | 15 W  | 960 lm        | 4000 K      | >90 | 10°   | Grey      |
| LG0 302A1 4 | COB CREE | 15 W  | 960 lm        | 4000 K      | >90 | 10°   | Dark grey |