

# Roll XL

## LG3 105A3 \_

### Technical description

LED fitting for ceilings. Body in die cast aluminium. Anodized aluminium reflector with high luminous efficiency. This fitting is equipped with integrated LED modules.  
Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100. Optics in anodized aluminium.  
LED light source CREE COB and colour temperature ( 2700K ).  
Very high coefficient of rendering >90CRI.

### Supply

Driver included.  
Input voltage 220-240 V AC/50-60Hz  
Temperature -20° +40°  
Life 30000h / 25°

### Installation

Ceiling.

### Size (mm)


200 x 200 x 240

### Colour

White ☐ 1 Grey ☐ 2 Dark grey ☐ 4



IP20



| Code        | Source   | Power | Luminous Flux | Temperature | CRI | Beams | Colour    |
|-------------|----------|-------|---------------|-------------|-----|-------|-----------|
| LG3 105A3 1 | COB CREE | 35 W  | 2466 lm       | 2700 K      | >90 | 15°   | White     |
| LG3 105A3 2 | COB CREE | 35 W  | 2466 lm       | 2700 K      | >90 | 15°   | Grey      |
| LG3 105A3 4 | COB CREE | 35 W  | 2466 lm       | 2700 K      | >90 | 15°   | Dark grey |