

Product Name

LED Panel R

Technical description

LED fitting for false ceilings, body in die cast aluminium. Diffuser in white opaline PMMA with high luminous efficiency. This fitting is equipped with integrated LED modules.
 Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100. Optics in anodized aluminium.
 LED light source and colour temperature (4000K Neutral White).
 Very high coefficient of rendering >80CRI.
 UGR < 19

Supply

External driver included.
 Input voltage 220-240 VAC/50-60Hz
 Temperature -20° +40°
 Life 50000h / 25°

Installation

Recessed for ceiling.



Size (mm)

295 x 1195 x 9

Color

White 1

CE **IP40** **RoHS** **2,9 Kg** **Flicker Free** **LED** **UGR < 19**



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
LLPR240BABL10040	LED	40 W	4000 lm	4000 K	>80	UGR <19	White

Accessories



Suspension kit
LKITA00000000022



Drywall recessed springs
LKITA00000000023



Ceiling frame (295x1195)
LKITA00000000091



Wall mounting kit
LKITA00000000026



Emergency Kit
LKITA00000000086



Driver DALI
LKITA00000000087