

Product Name

R1

(External driver)

Technical description

This fitting is suitable for wall or ceiling application. R1 is equipped with the latest LED technology that, combined with the choice of different optics, it ensures high performance lighting in the name of energy sustainability. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket and goniometer in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Silicone gaskets. Silicone gaskets. On request, tempered glass sodium-calcium type, 3 mm thickness, 91% transparency and IK07.

LED light source (lumileds), colour temperature (4000 K Neutral White).

High coefficient of performance chromatic CRI>80. Optic in optical PC.

Supply

External driver in ON-OFF, dimmable or DALI.

Voltage 220-240V AC 50/60Hz.

Temperature -40° +45°

Installation

Wall and ceiling.

Applications

Facades decoration, Commercial areas, Parkings, Warehouses, Advertising installations

Size (mm)



348 x 190 x 94

Colour

Dark grey **4**

Decay of the luminous flux

≥100.000 hr L90B10



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L00R140S8BL40110	LED	110 W	10379 lm	17600 lm	4000 K	>80	S8	Dark grey	-
L00R140S8DI40110	LED	110 W	10379 lm	17600 lm	4000 K	>80	S8	Dark grey	Dimmer
L00R140S8DA40110	LED	110 W	10379 lm	17600 lm	4000 K	>80	S8	Dark grey	DALI

Accessories



Cable with connector
Ca. 2m/Co. IP 2 poli
LKITA00000000040
Ca. 2m/Co. IP 3 poli
LKITA00000000041



Ceiling Kit
LKITA00000000060
Galvanised iron
LKITA00000000061
Inox



Pole connection A
Max 4 x R
LKITA00000040001



Fast connector
IP 2 poles
LKITA00000000017



Fast connector
IP 3 poles
LKITA00000000003



Pole connection B
LKITA00000040109

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.